


Specifications



| MODELS | GS™-2046 | | GS™-2646 | | GS™-3246 | |
|--|----------|---------------|----------|---------------|----------|---------------|
| | Metric | US | Metric | US | Metric | US |
| Working height maximum* | 8.10 m | 26 ft | 9.92 m | 32 ft | 11.75 m | 38 ft |
| A Platform height maximum | 6.10 m | 20 ft | 7.92 m | 26 ft | 9.75 m | 32 ft |
| B Platform height stowed | 1.04 m | 3 ft 4.8 in | 1.16 m | 3 ft 9.6 in | 1.29 m | 4 ft 2.75 in |
| C Platform length - outside | 2.26 m | 7 ft 5 in | 2.26 m | 7 ft 5 in | 2.26 m | 7 ft 5 in |
| extended | 3.18 m | 10 ft 5 in | 3.18 m | 10 ft 5 in | 3.18 m | 10 ft 5 in |
| Slide-out platform extension deck | 0.91 m | 3 ft | 0.91 m | 3 ft | 0.91 m | 3 ft |
| D Platform width - outside | 1.15 m | 3 ft 9.3 in | 1.15 m | 3 ft 9.3 in | 1.15 m | 3 ft 9.3 in |
| Guardrail height | 1.09 m | 3 ft 7 in | 1.09 m | 3 ft 7 in | 1.09 m | 3 ft 7 in |
| Toeboard height | 0.15 m | 6 in | 0.15 m | 6 in | 0.15 m | 6 in |
| E Height - stowed: folding guardrails | 2.13 m | 7 ft | 2.26 m | 7 ft 5 in | 2.39 m | 7 ft 10 in |
| rails folded | 1.55 m | 5 ft 1 in | 1.68 m | 5 ft 6 in | 1.80 m | 5 ft 11 in |
| F Length - stowed | 2.41 m | 7 ft 11 in | 2.41 m | 7 ft 11 in | 2.41 m | 7 ft 11 in |
| extended | 3.31 m | 10 ft 10.5 in | 3.31 m | 10 ft 10.5 in | 3.31 m | 10 ft 10.5 in |
| G Width | 1.17 m | 3 ft 10 in | 1.17 m | 3 ft 10 in | 1.17 m | 3 ft 10 in |
| H Wheelbase | 1.85 m | 6 ft 1 in | 1.85 m | 6 ft 1 in | 1.85 m | 6 ft 1 in |
| I Ground clearance - centre | 0.10 m | 4 in | 0.10 m | 4 in | 0.10 m | 4 in |
| J - with pothole guards deployed | 0.02 m | 0.75 in | 0.02 m | 0.75 in | 0.02 m | 0.75 in |

| PRODUCTIVITY | | | | | | |
|---------------------------------------|------------------|----------------|------------------|----------------|------------------|----------------|
| Maximum platform occupancy** - indoor | 2 | 2 | 2 | 2 | 2 | 2 |
| - outdoor | 2 | 2 | 2 | 2 | 1 | 1 |
| Lift capacity | 544 kg | 1,200 lbs | 454 kg | 1,000 lbs | 318 kg | 700 lbs |
| Lift capacity - extension deck | 113 kg | 250 lbs | 113 kg | 250 lbs | 113 kg | 250 lbs |
| Drive speed - stowed | 3.5 km/h | 2.2 mph | 3.5 km/h | 2.2 mph | 3.5 km/h | 2.2 mph |
| Drive speed - raised | 0.8 km/h | 0.5 mph | 0.8 km/h | 0.5 mph | 0.8 km/h | 0.5 mph |
| Gradeability - stowed*** | 30% | 30% | 30% | 30% | 25% | 25% |
| Turning radius - inside | zero | zero | zero | zero | zero | zero |
| Turning radius - outside | 2.29 m | 7 ft 6 in | 2.29 m | 7 ft 6 in | 2.29 m | 7 ft 6 in |
| Raise / lower speed | 30 / 33 sec | 30 / 33 sec | 30 / 38 sec | 30 / 38 sec | 57 / 35 sec | 57 / 35 sec |
| Controls | proportional | | proportional | | proportional | |
| Drive | dual front wheel | | dual front wheel | | dual front wheel | |
| Multiple disc brakes | dual rear wheel | | dual rear wheel | | dual rear wheel | |
| Tyres - solid non-marking | 38 x 13 x 28 cm | 15 x 5 x 11 in | 38 x 13 x 28 cm | 15 x 5 x 11 in | 38 x 13 x 28 cm | 15 x 5 x 11 in |

| POWER | | | | | | |
|---------------------------|-----------------------------------|----------|--------------------------------|----------|--------------------------------|---------|
| Power source | 24V DC (four 6V 225 Ah batteries) | | 24V (four 6V 225 Ah batteries) | | 24V (four 6V 225 Ah batteries) | |
| Hydraulic system capacity | 14.2 L | 3.75 gal | 14.2 L | 3.75 gal | 17 L | 4.5 gal |

| WEIGHT**** | | | | | | |
|------------|----------|-----------|----------|-----------|----------|-----------|
| | 1,974 kg | 4,351 lbs | 2,447 kg | 5,395 lbs | 2,812 kg | 6,200 lbs |

| STANDARDS COMPLIANCE | ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10 | | | | | |
|----------------------|---|--|--|--|--|--|
|----------------------|---|--|--|--|--|--|

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** CE/AUS markets: Two person maximum occupancy on all models. GS-3246 outdoor maximum occupancy is one person.
 *** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards.

Features

STANDARD FEATURES

MEASUREMENTS

GS™-2046

- 8.10 m (26 ft) working height
- Up to 545 kg (1,200 lbs) lift capacity

GS™-2646

- 9.92 m (32 ft) working height
- Up to 454 kg (1,000 lbs) lift capacity

GS™-3246

- 11.75 m (38 ft) working height
- Up to 318 kg (700 lbs) lift capacity

PRODUCTIVITY

- 2.26 m x 1.15 m (7 ft 5 in x 3 ft 9 in) steel platform
- 0.91 m (3 ft) extension deck
- Folding rails with full height swing gate
- Dual front wheel drive
- Proportional lift and drive
- Platform control with battery charge indicator and diagnostic display
- Onboard diagnostic system
- Lanyard attachment points
- Manual platform lowering valve
- Emergency stop at both platform and ground controls
- Rear wheel multiple disc brakes
- Front wheel hydraulic dynamic braking
- Brake release
- Drive speed interlock
- Swing-out component tray
- Solid non-marking tyres
- Pothole guards
- Tilt alarm
- Descent alarm
- Electronic horn
- Hour meter
- Dual flashing beacons
- Motion alarm

POWER

- 24 V DC (four 6 V 225 Ah batteries)
- Universal 20 amp smart charger

OPTIONS & ACCESSORIES

PRODUCTIVITY

- Air line to platform
- Pipe cradle (GS™-2646)
- Panel mounted, recessed charger receptacle
- Platform work lights
- Automotive horn

POWER OPTIONS

- Maintenance-free batteries
- EE rating
- 240 V power to platform



Genie Australia – Toll free number 1800 788 633

Brisbane (Head Office)
33 Kimberley Street
Darra QLD 4076

Sydney
74 Glendenning Road
Glendenning NSW 2761

Melbourne
374 Hammond Road
Dandenong VIC 3175

Perth
126 Sheffield Road
Welshpool WA 6106

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington
98073-9730

Distributed by:

